

Fast Set

(Liquid Accelerator)

DESCRIPTION:

Fast Set liquid accelerator is used to speed up the set time of Portland cement mixes. **Fast Set** provides and early hydration of Portland cement and aids in the attainment of the required strength and durability of cured concrete. **Fast Set** can also be used as a waterproofing plug or slush when substituted for the water normally used in Portland cement and sand mix. It can be used under adverse conditions even under water.

FEATURES & BENEFITS:

Features:

- Provides early hydration
- Accelerates set
- Reduces shrinkage
- Water retention

Benefits:

- Attainment of early strength
- Increases rate of hardening
- More durable, water resistance
- Uniform curing, less cracking & crazing

CHARACTERISTICS AND TECHNICAL DATA

Appearance...	Clear to milky liquid
Clean-up...	Soap and water
Boiling point...	212°F
Solubility in H ₂ O...	Dilutable
pH...	9-10
Specific gravity...	1.2

INSTRUCTIONS:

Mortar, Stucco, Deck Coatings, Marcite Mixes— Add **Fast Set** liquid accelerator directly to the mixing water for each batch. DO NOT ADD FAST SET DIRECTLY TO THE CEMENT. Read label for specific amounts.

Waterproofing Compound (leak stop)— Cut back and down in crack or hole where water is seeping through sufficiently to receive material. Dry mix 8 parts of fresh, Type 1 Portland cement, or high early cement, to one part clean, dry, sharp sand. Take 1½ cups of this mix and add enough **Fast Set** to dampen. Remove mix from container and kneed in your hands. Mix should be stiff like putty. If mix is thin, add more dry mix. When mix starts to get warm, smear portion of it in the spot that is to be plugged to ensure a good bond. When mix gets hot, jam it in place and apply steady pressure with a cloth or wood block for 30 seconds.

PACKAGING:

- 1-Gallon Containers (4 1-gal per case / 40 cases per pallet)
- 5-Gallon Pails (36 Pails per pallet)
- 55-Gallon Drums

PRECAUTIONS:

- Keep from freezing.
- AVOID contact with skin and eyes. Flush affected area thoroughly with water.
- DO NOT ingest. If ingested, induce vomiting.
- **Keep out of reach of children.**

ICT Corporation

2410 McJunkin Road * Lakeland, FL 33803

(Nationwide): 888-296-5236 * (Local): 863-665-8787 *(Fax): 863-666-2768

(Email): info@innovativeconcrete.com

www.innovativeconcrete.com

All Innovative Concrete Technology Corp. products are manufactured with the finest raw materials. Shelf life is 2 years from the date of manufacturing when maintained in protected storage of 50°F to 90°F. It is the applicator's responsibility to determine the appropriate use of the product. All recommendations and suggestions are made without warranty, express or implied, since conditions of use are beyond ICT's control. ICT Corp. disclaims any liability incurred in connection with the use of these data or suggestions.