



ICT TECHNICALS

Color Fast

(Liquid Color Additive)

690

USE:

Color Fast liquid additive is designed to incorporate color into the Texture-Krete 2000 Deck System, Deck Mix H2O, Super Deck Mix H2O, Stamp It 4000, and Micro Top 5000. When blended with the ICT Powder of choice Color Fast additive allows the user to create most ICT colors for use as bases (grout lines) and colored texture or hand troweled finishes.

FEATURES & BENEFITS:

- Ensures Color uniformity/consistency throughout.
- Easy to use
- Available in 2 sizes (32 oz. bottle and 64 oz Super Concentrate Jug)
- Applicator can create custom colors
- Easy to ship and store
- Environmentally friendly with Low VOC's

<u>CHARACTERISTICS AND TECHNICAL DATA</u>	
<u>Liquid Properties</u>	<u>Test Results</u>
Freezing Point.....	30°F
Appearance Wet.....	Liquid based, color will vary
Coverage Color Fast....	4-6 oz per bag mix
Coverage Super Concentrate....	2 oz per bag mix
Clean Up.....	Warm Soapy Water
Shelf Life.....	2 yr min. (closed container)
V.O.C.....	less than 200 grams/liter
Packaging....	32 oz. bottles

MIXING/APPLICATION INSTRUCTIONS:

Shake container of colorant 1-2 minutes. Dispense 2 oz. of Super Concentrate or 4-6 oz of Regular into the properly measured Liquid Resin or Water per bag of desired ICT Powder. Mix into product according to product mixing instructions. Be sure to use the same amount into each mix to ensure color uniformity.

Humidity and temperature variances can cause color mismatches. It is best to complete the job in one day or find a stopping point where slight color variations can be disguised. ICT Color Fast is not UV stable and must be sealed with either ICT Color Seal H2O Pro, Crystal Clear H2O, Crystal Coat SB, or Ure-Seal.

PRECAUTIONS:

- Keep from freezing
- Avoid contact with skin and eyes
- Do not store in direct sunlight
- Do not take internally

KEEP OUT OF THE REACH OF CHILDREN



ICT Corporation

2410 McJunkin Road * Lakeland, FL 33803

(Nationwide): 888-296-5236 * (Local): 863-665-8787 *(Fax): 863-666-2768

(Email): info@innovativeconcrete.com

www.innovativeconcrete.com

All Innovative Concrete Technology Corp. products are manufactured with the finest raw materials. Shelf life is 2 years from the date of manufacturing when maintained in protected storage of 50°F to 90°F. It is the applicator's responsibility to determine the appropriate use of the product. All recommendations and suggestions are made without warranty, express or implied, since conditions of use are beyond ICT's control. ICT Corp. disclaims any liability incurred in connection with the use of these data or suggestions.