

# Safety Data Sheet


according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: December 11, 2019

## 1 Identification

- **Product identifier**
- **Trade name:** **150 URE-SEAL H2O Gloss Part B**  
**151 URE-SEAL H2O Natural Part B**  
**152 URE-SEAL H2O Mid Gloss Part B**
- **Other means of identification:** No other identifiers
- **Recommended use and restriction on use**
- **Recommended use:** Polyurethane resin
- **Restrictions on use:** No relevant information available.
- **Details of the supplier of the Safety Data Sheet**
- **Manufacturer/Supplier:**  
Innovative Concrete Technology Corp.  
2410 McJunkin Road  
Lakeland, FL 33803  
(863) 665-8787  
sales@innovativeconcrete.com
- **Emergency telephone number:**  
ChemTel Inc.  
(800)255-3924 (North America)  
+1 (813)248-0585 (International)

## 2 Hazard(s) identification

- **Classification of the substance or mixture**  
Acute Tox. 4 H332 Harmful if inhaled.  
Skin Sens. 1 H317 May cause an allergic skin reaction.  
STOT SE 3 H335 May cause respiratory irritation.
- **Label elements**
- **GHS label elements**  
The product is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms:**  
  
GHS07
- **Signal word:** Warning
- **Hazard statements:**  
H332 Harmful if inhaled.  
H317 May cause an allergic skin reaction.  
H335 May cause respiratory irritation.
- **Precautionary statements:**  
P261 Avoid breathing dust/fume/gas/mist/vapors/spray  
P271 Use only outdoors or in a well-ventilated area.  
P272 Contaminated work clothing must not be allowed out of the workplace.  
P280 Wear protective gloves.  
P302+P352 If on skin: Wash with plenty of soap and water.  
P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

(Cont'd. on page 2)

## Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: December 11, 2019

**Trade name: 150 URE-SEAL H2O Gloss Part B**  
**151 URE-SEAL H2O Natural Part B**  
**152 URE-SEAL H2O Mid Gloss Part B**

(Cont'd. of page 1)

P312 Call a poison center/doctor if you feel unwell.  
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.  
P363 Wash contaminated clothing before reuse.  
P403+P233 Store in a well-ventilated place. Keep container tightly closed.  
P405 Store locked up.  
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Other hazards** There are no other hazards not otherwise classified that have been identified.

### 3 Composition/information on ingredients

· **Chemical characterization: Mixtures**

· **Components:**

28182-81-2	Hexamethylene diisocyanate, homopolymer ⚠ Acute Tox. 4, H332; Skin Sens. 1, H317; STOT SE 3, H335	60-80%
666723-27-9	Hydrophilic aliphatic polyisocyanate based on hexamethylene diisocyanate ⚠ Acute Tox. 4, H332; Skin Sens. 1, H317; STOT SE 3, H335	10-30%
98-94-2	cyclohexyldimethylamine ⚠ Flam. Liq. 3, H226 ⚠ Acute Tox. 3, H301; Acute Tox. 3, H331 ⚠ Skin Corr. 1B, H314; Eye Dam. 1, H318	0.1-1%
822-06-0	hexamethylene-di-isocyanate ⚠ Acute Tox. 3, H311; Acute Tox. 1, H330 ⚠ Resp. Sens. 1, H334 ⚠ Acute Tox. 4, H302; Skin Irrit. 2, H315; Eye Irrit. 2A, H319; Skin Sens. 1, H317; STOT SE 3, H335	<0.5%

· **Additional information:**

For the listed ingredient(s), the identity and/or exact percentage(s) are being withheld as a trade secret.

For the wording of the listed Hazard Statements, refer to section 16.

This product contains an amine neutralizing agent which is bound in the matrix of this product as a salt.

This amine salt is considered essentially unreactive at room temperature. Generation of amine vapors is expected when this product is processed (heated) during the drying/hardening of the coating.

### 4 First-aid measures

· **Description of first aid measures**

· **After inhalation:**

Supply fresh air; consult doctor in case of complaints.

Provide oxygen treatment if affected person has difficulty breathing.

· **After skin contact:**

Immediately remove any clothing soiled by the product.

Immediately wash with water and soap and rinse thoroughly.

If skin irritation or rash occurs: Get medical advice/attention.

· **After eye contact:**

Immediately remove contact lenses if possible.

(Cont'd. on page 3)

## Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: December 11, 2019

**Trade name: 150 URE-SEAL H2O Gloss Part B**  
**151 URE-SEAL H2O Natural Part B**  
**152 URE-SEAL H2O Mid Gloss Part B**

(Cont'd. of page 2)

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· **After swallowing:**

Rinse out mouth and then drink plenty of water.

Do not induce vomiting; immediately call for medical help.

· **Most important symptoms and effects, both acute and delayed:**

Breathing difficulty

Coughing

Allergic reactions

May cause respiratory irritation.

· **Danger:** Harmful if inhaled.

· **Indication of any immediate medical attention and special treatment needed:**

Medical supervision for at least 48 hours.

Treat symptomatically.

### 5 Fire-fighting measures

· **Extinguishing media**

· **Suitable extinguishing agents:**

CO<sub>2</sub>, extinguishing powder or water spray. Fight larger fires with water spray.

· **For safety reasons unsuitable extinguishing agents:** Water stream.

· **Special hazards arising from the substance or mixture**

During heating or in case of fire poisonous gases are produced.

· **Advice for firefighters**

· **Protective equipment:**

Wear self-contained respiratory protective device.

Do not inhale explosion gases or combustion gases.

Wear fully protective suit.

### 6 Accidental release measures

· **Personal precautions, protective equipment and emergency procedures**

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation.

Use respiratory protective device against the effects of fumes/dust/aerosol.

· **Environmental precautions**

Do not allow to enter sewers/ surface or ground water.

Inform respective authorities in case of seepage into water course or sewage system.

· **Methods and material for containment and cleaning up**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Ensure adequate ventilation.

Send for recovery or disposal in suitable receptacles.

· **Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

(Cont'd. on page 4)

# Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: December 11, 2019

**Trade name: 150 URE-SEAL H2O Gloss Part B**  
**151 URE-SEAL H2O Natural Part B**  
**152 URE-SEAL H2O Mid Gloss Part B**

(Cont'd. of page 3)

## 7 Handling and storage

- **Handling**
- **Precautions for safe handling:**  
 Use only in well ventilated areas.  
 Avoid breathing dust.  
 Avoid breathing mist, vapors, or spray.  
 Avoid contact with the eyes and skin.  
 Open and handle receptacle with care.
- **Conditions for safe storage, including any incompatibilities**
- **Requirements to be met by storerooms and receptacles:**  
 Store in cool, dry conditions in well sealed receptacles.  
 Store in a well-ventilated place. Keep cool.  
 Store at 41-95 °F / 5-30 °C.
- **Information about storage in one common storage facility:**  
 Store away from foodstuffs.  
 Store away from water.
- **Specific end use(s)** No relevant information available.

## 8 Exposure controls/personal protection

- **Control parameters**
- **Components with limit values that require monitoring at the workplace:**

### 98-94-2 cyclohexyldimethylamine

EV (Canada)	Short-term value: 26 mg/m <sup>3</sup> , 5 ppm
-------------	--

### 822-06-0 hexamethylene-di-isocyanate

REL (USA)	Long-term value: 0.035 mg/m <sup>3</sup> , 0.005 ppm Ceiling limit value: 0.14* mg/m <sup>3</sup> , 0.02* ppm *10-min
-----------	---

TLV (USA)	Long-term value: 0.034 mg/m <sup>3</sup> , 0.005 ppm BEI
-----------	---

EL (Canada)	Long-term value: 0.005 ppm Ceiling limit value: 0.01 ppm S(R)
-------------	---

EV (Canada)	Long-term value: 0.005 ppm Ceiling limit value: 0.02 ppm
-------------	---

LMPE (Mexico)	Long-term value: 0.005 ppm
---------------	----------------------------

- **Exposure controls**
- **General protective and hygienic measures:**  
 The usual precautionary measures for handling chemicals should be followed.  
 Keep away from foodstuffs, beverages and feed.  
 Immediately remove all soiled and contaminated clothing.  
 Wash hands before breaks and at the end of work.  
 Do not breathe dust/fume/gas/mist/vapors/spray.

(Cont'd. on page 5)

# Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: December 11, 2019

**Trade name: 150 URE-SEAL H2O Gloss Part B**  
**151 URE-SEAL H2O Natural Part B**  
**152 URE-SEAL H2O Mid Gloss Part B**

(Cont'd. of page 4)

- Avoid contact with the eyes and skin.
- **Engineering controls:** Provide adequate ventilation.
- **Breathing equipment:** Suitable respiratory protective device recommended.
- **Protection of hands:**



Protective gloves

- **Material of gloves**  
 Butyl rubber, BR  
 Nitrile rubber, NBR  
 Neoprene gloves
- **Eye protection:**



Safety glasses

- **Body protection:** Protective work clothing
- **Limitation and supervision of exposure into the environment**  
 No relevant information available.
- **Risk management measures** No relevant information available.

## 9 Physical and chemical properties

### · Information on basic physical and chemical properties

#### · Appearance:

· <b>Form:</b>	Liquid
· <b>Color:</b>	Light yellow
· <b>Odor:</b>	Slight
· <b>Odor threshold:</b>	Not determined.

· <b>pH-value:</b>	Not determined.
· <b>Melting point/Melting range:</b>	Not determined.
· <b>Boiling point/Boiling range:</b>	Not determined.

· **Flash point:** 185 °C (365 °F)

· **Flammability (solid, gaseous):** Not applicable.

· **Auto-ignition temperature:** 445 °C (833 °F)

· **Decomposition temperature:** 181 °C (357.8 °F)

· **Danger of explosion:** Product does not present an explosion hazard.

#### · Explosion limits

· <b>Lower:</b>	Not determined.
· <b>Upper:</b>	Not determined.

· **Oxidizing properties:** Not determined.

(Cont'd. on page 6)

## Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: December 11, 2019

**Trade name: 150 URE-SEAL H2O Gloss Part B**  
**151 URE-SEAL H2O Natural Part B**  
**152 URE-SEAL H2O Mid Gloss Part B**

(Cont'd. of page 5)

· <b>Vapor pressure:</b>	Not determined.
· <b>Density:</b>	
<b>Relative density:</b>	1.15
<b>Vapor density:</b>	Not determined.
<b>Evaporation rate:</b>	Not determined.
· <b>Solubility in / Miscibility with Water:</b>	Not miscible or difficult to mix.
· <b>Partition coefficient (n-octanol/water):</b>	Not determined.
· <b>Viscosity</b>	
<b>Dynamic at 20 °C (68 °F):</b>	800 mPas
<b>Kinematic:</b>	Not determined.
· <b>Other information</b>	No relevant information available.

### 10 Stability and reactivity

- **Reactivity:** No relevant information available.
- **Chemical stability:** Stable under normal temperatures and pressures.
- **Thermal decomposition / conditions to be avoided:**  
No decomposition if used and stored according to specifications.
- **Possibility of hazardous reactions**  
Reacts with light alloys.  
Reacts with strong alkali.  
Reacts with amines.  
Reacts with alcohols.
- **Conditions to avoid**  
Excessive heat.  
Do not allow product to freeze.
- **Incompatible materials**  
Alkalis.  
Alcohols  
Amines  
Water
- **Hazardous decomposition products**  
Under fire conditions only:  
Carbon monoxide and carbon dioxide  
Nitrogen oxides  
Isocyanate  
Hydrogen cyanide (prussic acid)

### 11 Toxicological information

- **Information on toxicological effects**

(Cont'd. on page 7)

# Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: December 11, 2019

**Trade name: 150 URE-SEAL H2O Gloss Part B**  
**151 URE-SEAL H2O Natural Part B**  
**152 URE-SEAL H2O Mid Gloss Part B**

(Cont'd. of page 6)

· **Acute toxicity:** Harmful if inhaled.

· **LD/LC50 values that are relevant for classification:**

**28182-81-2 Hexamethylene diisocyanate, homopolymer**

Oral	LD50	>5000 mg/kg (rat)
Dermal	LD50	>5000 mg/kg (rabbit)

**98-94-2 cyclohexyldimethylamine**

Oral	LD50	272 mg/kg (rat)
Dermal	LD50	>400 mg/kg (rat)
Inhalative	LC50/4h	4.45 mg/l (rat)

**822-06-0 hexamethylene-di-isocyanate**

Oral	LD50	959 mg/kg (rat)
Dermal	LD50	593 mg/kg (rat)
Inhalative	LC50/4h	124 mg/l (rat)

· **Primary irritant effect:**

- **On the skin:** Based on available data, the classification criteria are not met.
- **On the eye:** Based on available data, the classification criteria are not met.
- **Sensitization:** Sensitization possible through skin contact.

· **IARC (International Agency for Research on Cancer):**

None of the ingredients are listed.

· **NTP (National Toxicology Program):**

None of the ingredients are listed.

· **OSHA-Ca (Occupational Safety & Health Administration):**

None of the ingredients are listed.

· **Probable route(s) of exposure:**

- Ingestion.
- Inhalation.
- Eye contact.
- Skin contact.

- **Germ cell mutagenicity:** Based on available data, the classification criteria are not met.
- **Carcinogenicity:** Based on available data, the classification criteria are not met.
- **Reproductive toxicity:** Based on available data, the classification criteria are not met.
- **STOT-single exposure:** May cause respiratory irritation.
- **STOT-repeated exposure:** Based on available data, the classification criteria are not met.
- **Aspiration hazard:** Based on available data, the classification criteria are not met.

## 12 Ecological information

- **Toxicity**
- **Aquatic toxicity** Harmful to aquatic life with long lasting effects.
- **Persistence and degradability** Not easily biodegradable
- **Bioaccumulative potential:** Non significant accumulation in organisms
- **Mobility in soil:** No relevant information available.

(Cont'd. on page 8)

## Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: December 11, 2019

**Trade name:** 150 URE-SEAL H2O Gloss Part B  
 151 URE-SEAL H2O Natural Part B  
 152 URE-SEAL H2O Mid Gloss Part B

· **Other adverse effects** No relevant information available.

(Cont'd. of page 7)

### 13 Disposal considerations

· **Waste treatment methods**

· **Recommendation:**

The user of this material has the responsibility to dispose of unused material, residues and containers in compliance with all relevant local, state and federal laws and regulations regarding treatment, storage and disposal for hazardous and nonhazardous wastes.

· **Uncleaned packagings**

· **Recommendation:** Disposal must be made according to official regulations.

### 14 Transport information

· **UN-Number**

· DOT, ADR/RID/ADN, IMDG, IATA Not regulated.

· **UN proper shipping name**

· DOT Not regulated.

· ADR/RID/ADN, IMDG, IATA Not regulated.

· **Transport hazard class(es)**

· DOT, ADR/RID/ADN, IMDG, IATA

· Class Not regulated.

· **Packing group**

· DOT, ADR/RID/ADN, IMDG, IATA Not regulated.

· **Environmental hazards**

· Marine pollutant: No

· **Special precautions for user**

Not applicable.

· **Transport in bulk according to Annex II of**

**MARPOL73/78 and the IBC Code** Not applicable.

### 15 Regulatory information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**

· United States (USA)

· SARA

· **Section 302 (extremely hazardous substances):**

None of the ingredients are listed.

(Cont'd. on page 9)



# Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: December 11, 2019

**Trade name: 150 URE-SEAL H2O Gloss Part B**  
**151 URE-SEAL H2O Natural Part B**  
**152 URE-SEAL H2O Mid Gloss Part B**

(Cont'd. of page 8)

· **Section 355 (extremely hazardous substances):**

None of the ingredients are listed.

· **Section 313 (Specific toxic chemical listings):**

None of the ingredients are listed.

· **TSCA (Toxic Substances Control Act)**

All ingredients are listed or exempt.

· **Proposition 65 (California)**

· **Chemicals known to cause cancer:**

None of the ingredients are listed.

· **Chemicals known to cause developmental toxicity for females:**

None of the ingredients are listed.

· **Chemicals known to cause developmental toxicity for males:**

None of the ingredients are listed.

· **Chemicals known to cause developmental toxicity:**

None of the ingredients are listed.

· **EPA (Environmental Protection Agency):**

None of the ingredients are listed.

· **IARC (International Agency for Research on Cancer):**

None of the ingredients are listed.

· **Canadian Domestic Substances List (DSL):**

All ingredients are listed or exempt.

## 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Abbreviations and acronyms:**

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road  
 IMDG: International Maritime Code for Dangerous Goods  
 DOT: US Department of Transportation  
 IATA: International Air Transport Association  
 CAS: Chemical Abstracts Service (division of the American Chemical Society)  
 LC50: Lethal concentration, 50 percent  
 LD50: Lethal dose, 50 percent  
 OSHA: Occupational Safety & Health Administration  
 Flam. Liq. 3: Flammable liquids – Category 3  
 Acute Tox. 3: Acute toxicity – Category 3  
 Acute Tox. 1: Acute toxicity – Category 1  
 Acute Tox. 4: Acute toxicity – Category 4  
 Skin Corr. 1B: Skin corrosion/irritation – Category 1B  
 Skin Irrit. 2: Skin corrosion/irritation – Category 2  
 Eye Dam. 1: Serious eye damage/eye irritation – Category 1  
 Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A  
 Resp. Sens. 1: Respiratory sensitisation – Category 1  
 Skin Sens. 1: Skin sensitisation – Category 1  
 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

(Cont'd. on page 10)

## Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: December 11, 2019

**Trade name: 150 URE-SEAL H2O Gloss Part B**  
**151 URE-SEAL H2O Natural Part B**  
**152 URE-SEAL H2O Mid Gloss Part B**

(Cont'd. of page 9)

· **Sources**

Website, European Chemicals Agency ([echa.europa.eu](http://echa.europa.eu))

Website, US EPA Substance Registry Services ([ofmpub.epa.gov/sorinternet/registry/substreg/home/overview/home.do](http://ofmpub.epa.gov/sorinternet/registry/substreg/home/overview/home.do))

Website, Chemical Abstracts Registry, American Chemical Society ([www.cas.org](http://www.cas.org))

Patty's Industrial Hygiene, 6th ed., Rose, Vernon, ed. ISBN: 978-0-470-07488-6

Casarett and Doull's Toxicology: The Basic Science of Poisons, 8th Ed., Klaasen, Curtis D., ed., ISBN: 978-0-07-176923-5.

Safety Data Sheets, Individual Manufacturers

SDS Prepared by:

ChemTel Inc.

1305 North Florida Avenue

Tampa, Florida USA 33602-2902

Toll Free North America 1-888-255-3924 Intl. +01 813-248-0573

Website: [www.chemtelinc.com](http://www.chemtelinc.com)