

Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: April 23, 2020

1 Identification

- **Product identifier**
- **Trade name: 220 Color Seal H2O Pro**
- **Other means of identification:**
 - 220-AT Autumn Tan
 - 220-BW Beachwood
 - 220-CB Cabo Beach
 - 220-CC Caribbean Cream
 - 220-DB Deep Base
 - 220-DN Deep Night
 - 220-GR Graystone
 - 220-IC Irish Cream
 - 220-MB Medium Base
 - 220-MO Mocca
 - 220-NA Natural
 - 220-NB Neutral Base
 - 220-OA Oasis
 - 220-OS Ocean Sand
 - 220-OY Oyster
 - 220-SC Southern Clay
 - 220-SM Smoke
 - 220-SN Sunset
 - 220-WH White
- **Recommended use and restriction on use**
- **Recommended use:** Concrete Sealer and Protector
- **Restrictions on use:** No relevant information available.
- **Details of the supplier of the Safety Data Sheet**
- **Manufacturer/Supplier:**
 - Innovative Concrete Technology Corp.
 - 2410 McJunkin Road
 - Lakeland, FL 33803
 - (863) 665-8787
 - sales@innovativeconcrete.com
- **Emergency telephone number:**
 - ChemTel
 - (800)255-3924 (North America)
 - +1 (813)248-0585 (International)

2 Hazard(s) identification

- **Classification of the substance or mixture**
 - Skin Sens. 1 H317 May cause an allergic skin reaction.
- **Label elements**
- **GHS label elements**
 - The product is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms:**

(Cont'd. on page 2)

Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: April 23, 2020

Trade name: 220 Color Seal H2O Pro

(Cont'd. of page 1)



GHS07

· **Signal word:** Warning

· **Hazard statements:**

H317 May cause an allergic skin reaction.

· **Precautionary statements:**

P261 Avoid breathing dust/fume/gas/mist/vapors/spray

P272 Contaminated work clothing must not be allowed out of the workplace.

P280 Wear protective gloves.

P302+P352 If on skin: Wash with plenty of soap and water.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P363 Wash contaminated clothing before reuse.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Other hazards** There are no other hazards not otherwise classified that have been identified.

3 Composition/information on ingredients

· **Chemical characterization:** Mixtures

· **Components:**

13463-67-7	Titanium dioxide	<20%
1332-58-7	Kaolin	<5%
1309-37-1	Diiron trioxide / iron (III) oxide	<1%
1344-28-1	Aluminum oxide	<1%
7631-86-9	Silicon dioxide	<1%
1333-86-4	Carbon black	<1%
26172-55-4	5-chloro-2-methyl-2H-isothiazol-3-one	<0.05%
	Acute Tox. 3, H301; Acute Tox. 3, H311; Acute Tox. 3, H331 Skin Corr. 1B, H314 Skin Sens. 1, H317	

· **Additional information:**

Non-classification as a carcinogen is based on non-inhalable form of product. IARC listings for carbon black and titanium dioxide note that the substance must be respirable.

For the listed ingredient(s), the identity and/or exact percentage(s) are being withheld as a trade secret.

For the wording of the listed Hazard Statements, refer to section 16.

4 First-aid measures

· **Description of first aid measures**

· **After inhalation:**

Respiration of particulates is unlikely during normal usage.

Supply fresh air; consult doctor in case of complaints.

· **After skin contact:**

(Cont'd. on page 3)

Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: April 23, 2020

Trade name: 220 Color Seal H2O Pro

(Cont'd. of page 2)

Wash with soap and water.

If skin irritation or rash occurs: Get medical advice/attention.

· **After eye contact:**

Remove contact lenses if worn.

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· **After swallowing:**

Rinse out mouth and then drink plenty of water.

Do not induce vomiting; immediately call for medical help.

· **Most important symptoms and effects, both acute and delayed:**

Nausea in case of ingestion.

May cause gastro-intestinal irritation if ingested.

Slight irritant effect on eyes.

Allergic reactions

· **Indication of any immediate medical attention and special treatment needed:**

Contains 5-chloro-2-methyl-2H-isothiazol-3-one (CMIT). May produce an allergic reaction.

Treat skin and mucous membrane with antihistamine and corticoid preparations.

5 Fire-fighting measures

· **Extinguishing media**

· **Suitable extinguishing agents:**

The product is not flammable.

Use fire fighting measures that suit the environment.

· **For safety reasons unsuitable extinguishing agents:** None.

· **Special hazards arising from the substance or mixture**

Formation of toxic gases is possible during heating or in case of fire.

· **Advice for firefighters**

· **Protective equipment:**

Wear self-contained respiratory protective device.

Wear fully protective suit.

6 Accidental release measures

· **Personal precautions, protective equipment and emergency procedures**

Ensure adequate ventilation.

Use personal protective equipment as required.

Particular danger of slipping on leaked/spilled product.

· **Environmental precautions** Avoid release to the environment.

· **Methods and material for containment and cleaning up**

Towel or mop up material and collect in a suitable container.

For larger spills, add sawdust, chalk or other inert binding material, then sweep up and discard.

Dispose of the collected material according to regulations.

· **Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

(Cont'd. on page 4)

Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: April 23, 2020

Trade name: 220 Color Seal H2O Pro

(Cont'd. of page 3)

7 Handling and storage

- **Handling**
- **Precautions for safe handling:**
 - Use only in well ventilated areas.
 - Avoid splashes or spray in enclosed areas.
 - Keep out of reach of children.
 - Avoid contact with the eyes and skin.
 - Avoid breathing mist, vapors, or spray.
- **Conditions for safe storage, including any incompatibilities**
- **Requirements to be met by storerooms and receptacles:**
 - Store in cool, dry conditions in well sealed receptacles.
 - Do not allow product to freeze.
- **Information about storage in one common storage facility:** Store away from foodstuffs.
- **Further information about storage conditions:** Protect from heat and direct sunlight.
- **Specific end use(s)** No relevant information available.

8 Exposure controls/personal protection

· Control parameters

· Components with limit values that require monitoring at the workplace:

13463-67-7 Titanium dioxide

PEL (USA)	Long-term value: 15* mg/m ³ *total dust
REL (USA)	See Pocket Guide App. A
TLV (USA)	Long-term value: 10 mg/m ³
EL (Canada)	Long-term value: 10* 3** mg/m ³ *total dust; **respirable fraction; IARC 2B
EV (Canada)	Long-term value: 10 mg/m ³ total dust
LMPE (Mexico)	Long-term value: 10 mg/m ³ A4

1332-58-7 Kaolin

PEL (USA)	Long-term value: 15* 5** mg/m ³ *total dust **respirable fraction
REL (USA)	Long-term value: 10* 5** mg/m ³ *total dust **respirable fraction
TLV (USA)	Long-term value: 2* mg/m ³ E; as respirable fraction
EL (Canada)	Long-term value: 2 mg/m ³
EV (Canada)	Long-term value: 2(D) mg/m ³ respirable
LMPE (Mexico)	Long-term value: 2* mg/m ³ A4, *fracción respirable

1309-37-1 Diiron trioxide / iron (III) oxide

(Cont'd. on page 5)

Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: April 23, 2020

Trade name: 220 Color Seal H2O Pro

(Cont'd. of page 4)

PEL (USA)	Long-term value: 10* mg/m ³ *Fume
REL (USA)	Long-term value: 5 mg/m ³ Dust & fume, as Fe
TLV (USA)	Long-term value: 5* mg/m ³ *as respirable fraction
EL (Canada)	Short-term value: 10** mg/m ³ Long-term value: 5* 10*** 3**** mg/m ³ *dust & fume**fume; Rouge: ***total dust****resp.
EV (Canada)	Long-term value: 5* 10** mg/m ³ *respirable, including Rouge,**total dust
LMPE (Mexico)	Long-term value: 5* mg/m ³ A4, *fracción respirable

1344-28-1 Aluminum oxide

PEL (USA)	Long-term value: 15*; 5** mg/m ³ *Total dust; ** Respirable fraction
REL (USA)	Long-term value: 10* 5** mg/m ³ as Al*Total dust**Respirable/pyro powd./welding f.
TLV (USA)	Long-term value: 1* mg/m ³ as Al; *as respirable fraction
EL (Canada)	Long-term value: 1.0 mg/m ³ respirable, as Al
EV (Canada)	Long-term value: 10 mg/m ³ total dust
LMPE (Mexico)	Long-term value: 1* mg/m ³ A4, *fracción respirable

7631-86-9 Silicon dioxide

NIOSH REL (USA)	Long-term value: 6 mg/m ³
OSHA PEL (USA)	Long-term value: 80 mg/m ³

1333-86-4 Carbon black

PEL (USA)	Long-term value: 3.5 mg/m ³
REL (USA)	Long-term value: 3.5* mg/m ³ *0.1 in presence of PAHs;See Pocket Guide Apps.A+C
TLV (USA)	Long-term value: 3* mg/m ³ *inhalable fraction
EL (Canada)	Long-term value: 3 mg/m ³ IARC 2B
EV (Canada)	Long-term value: 3.5 mg/m ³
LMPE (Mexico)	Long-term value: 3* mg/m ³ A3, *fracción inhalable

· **Exposure controls**

· **General protective and hygienic measures:**

The usual precautionary measures for handling chemicals should be followed.

Keep away from foodstuffs, beverages and feed.

Do not eat, drink or smoke while using the product.

(Cont'd. on page 6)

Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: April 23, 2020

Trade name: 220 Color Seal H2O Pro

(Cont'd. of page 5)

- Wash hands before breaks and at the end of work.
- Avoid contact with the eyes and skin.
- Avoid breathing mist, vapors, or spray.
- **Engineering controls:** No relevant information available.
- **Breathing equipment:**
 Not required under normal conditions of use.
 In case of inadequate ventilation wear respiratory protection.
 A NIOSH approved dust respirator should be used for operations generating dust.

· **Protection of hands:**



Protective gloves

- The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
- **Eye protection:** Follow relevant national guidelines concerning the use of protective eyewear.
- **Body protection:** Protective work clothing
- **Limitation and supervision of exposure into the environment** No special requirements.
- **Risk management measures** No special requirements.

9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **Appearance:**

Form: Liquid
 Color: According to product specification

· **Odor:** Characteristic
 · **Odor threshold:** Not determined.

· **pH-value:** 8.5-9
 · **Melting point/Melting range:** Not determined.
 · **Boiling point/Boiling range:** Not determined.

· **Flash point:** Not applicable.

· **Flammability (solid, gaseous):** Not applicable.

· **Auto-ignition temperature:** Not determined.

· **Decomposition temperature:** Not determined.

· **Danger of explosion:** Product does not present an explosion hazard.

· **Explosion limits**

Lower: Not determined.
 Upper: Not determined.

· **Oxidizing properties:** Non-oxidizing.

· **Vapor pressure:** Not determined.

· **Density:**

Relative density: 1.19-1.31
 Vapor density: Not determined.
 Evaporation rate: Not determined.

(Cont'd. on page 7)

Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: April 23, 2020

Trade name: 220 Color Seal H2O Pro

(Cont'd. of page 6)

- **Solubility in / Miscibility with Water:** Soluble.
- **Partition coefficient (n-octanol/water):** Not determined.
- **Viscosity**
 - **Dynamic:** Not determined.
 - **Kinematic:** Not determined.
- **VOC content:** <100 g/l
- **Other information** No relevant information available.

10 Stability and reactivity

- **Reactivity:** No relevant information available.
- **Chemical stability:**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used and stored according to specifications.
- **Possibility of hazardous reactions**
Toxic fumes may be released if heated above the decomposition point.
- **Conditions to avoid**
Excessive heat.
Do not allow product to freeze.
- **Incompatible materials** No relevant information available.
- **Hazardous decomposition products**
Under fire conditions only:
Toxic metal compounds
Carbon monoxide and carbon dioxide

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:** Based on available data, the classification criteria are not met.
- **LD/LC50 values that are relevant for classification:** None.
- **Primary irritant effect:**
- **On the skin:** Based on available data, the classification criteria are not met.
- **On the eye:** Based on available data, the classification criteria are not met.
- **Sensitization:** Sensitizing effect by skin contact is possible with prolonged exposure.

· **IARC (International Agency for Research on Cancer):**

13463-67-7	Titanium dioxide	2B
1333-86-4	Carbon black	2B
14808-60-7	Quartz	1
111-42-2	2,2'-iminodiethanol	2B
75-21-8	Ethylene oxide	1
75-56-9	propylene oxide	2B
123-91-1	1,4-dioxane	2B

(Cont'd. on page 8)

Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: April 23, 2020

Trade name: 220 Color Seal H2O Pro

(Cont'd. of page 7)

· **NTP (National Toxicology Program):**

Present in trace quantities.

14808-60-7	Quartz
75-21-8	Ethylene oxide
75-56-9	propylene oxide
123-91-1	1,4-dioxane

· **OSHA-Ca (Occupational Safety & Health Administration):**

Present in trace quantities.

75-21-8	Ethylene oxide
---------	----------------

· **Probable route(s) of exposure:**

- Ingestion.
- Eye contact.
- Skin contact.

· **Germ cell mutagenicity:** Based on available data, the classification criteria are not met.

· **Carcinogenicity:**

Contains known or suspect carcinogens when inhaled. Product is in non-inhalable form and is nonclassifiable as a carcinogen.

· **Reproductive toxicity:** Based on available data, the classification criteria are not met.

· **STOT-single exposure:** Based on available data, the classification criteria are not met.

· **STOT-repeated exposure:** Based on available data, the classification criteria are not met.

· **Aspiration hazard:** Based on available data, the classification criteria are not met.

12 Ecological information

· **Toxicity**

- **Aquatic toxicity** No relevant information available.
- **Persistence and degradability** No relevant information available.
- **Bioaccumulative potential:** No relevant information available.
- **Mobility in soil:** No relevant information available.
- **Other adverse effects** No relevant information available.

13 Disposal considerations

· **Waste treatment methods**

· **Recommendation:**

Smaller quantities can be disposed of with household waste.

Small amounts may be diluted with plenty of water and washed away. Dispose of bigger amounts in accordance with Local Authority requirements.

The user of this material has the responsibility to dispose of unused material, residues and containers in compliance with all relevant local, state and federal laws and regulations regarding treatment, storage and disposal for hazardous and nonhazardous wastes.

· **Uncleaned packagings**

- **Recommendation:** Disposal must be made according to official regulations.

(Cont'd. on page 9)

Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: April 23, 2020

Trade name: 220 Color Seal H2O Pro

(Cont'd. of page 8)

14 Transport information

- **UN-Number**
 · DOT, ADR/RID/ADN, IMDG, IATA Not regulated.
- **UN proper shipping name**
 · DOT, ADR/RID/ADN, IMDG, IATA Not regulated.
- **Transport hazard class(es)**
 · DOT, ADR/RID/ADN, IMDG, IATA
 · Class Not regulated.
- **Packing group**
 · DOT, ADR/RID/ADN, IMDG, IATA Not regulated.
- **Environmental hazards**
 · Marine pollutant: No
- **Special precautions for user** Not applicable.
- **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code** Not applicable.

15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **United States (USA)**
- **SARA**

· **Section 302 (extremely hazardous substances):**

None of the ingredients are listed.

· **Section 313 (Specific toxic chemical listings):**

None of the ingredients are listed.

· **TSCA (Toxic Substances Control Act)**

All ingredients are listed or exempt.

· **Proposition 65 (California)**

· **Chemicals known to cause cancer:**

13463-67-7	Titanium dioxide
1333-86-4	Carbon black
14808-60-7	Quartz
111-42-2	2,2'-iminodiethanol
75-21-8	Ethylene oxide
75-56-9	propylene oxide
123-91-1	1,4-dioxane

· **Chemicals known to cause developmental toxicity for females:**

(Cont'd. on page 10)

Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: April 23, 2020

Trade name: 220 Color Seal H2O Pro

(Cont'd. of page 9)

75-21-8 Ethylene oxide

· **Chemicals known to cause developmental toxicity for males:**

75-21-8 Ethylene oxide

· **Chemicals known to cause developmental toxicity:**

75-21-8 Ethylene oxide

· **EPA (Environmental Protection Agency):**

None of the ingredients are listed.

· **IARC (International Agency for Research on Cancer):**

13463-67-7	Titanium dioxide	2B
1333-86-4	Carbon black	2B
14808-60-7	Quartz	1
111-42-2	2,2'-iminodiethanol	2B
75-21-8	Ethylene oxide	1
75-56-9	propylene oxide	2B
123-91-1	1,4-dioxane	2B

· **Canadian Domestic Substances List (DSL):**

All ingredients are listed or exempt.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Abbreviations and acronyms:**

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road
 IMDG: International Maritime Code for Dangerous Goods
 DOT: US Department of Transportation
 IATA: International Air Transport Association
 CAS: Chemical Abstracts Service (division of the American Chemical Society)
 LC50: Lethal concentration, 50 percent
 LD50: Lethal dose, 50 percent
 OSHA: Occupational Safety & Health Administration
 Acute Tox. 3: Acute toxicity – Category 3
 Skin Corr. 1B: Skin corrosion/irritation – Category 1B
 Skin Sens. 1: Skin sensitisation – Category 1

· **Sources**

Website, European Chemicals Agency (echa.europa.eu)
 Website, US EPA Substance Registry Services (ofmpub.epa.gov/sor internet/registry/substreg/home/overview/home.do)
 Website, Chemical Abstracts Registry, American Chemical Society (www.cas.org)
 Patty's Industrial Hygiene, 6th ed., Rose, Vernon, ed. ISBN: 978-0-470-07488-6
 Casarett and Doull's Toxicology: The Basic Science of Poisons, 8th Ed., Klaassen, Curtis D., ed., ISBN: 978-0-07-176923-5.
 Safety Data Sheets, Individual Manufacturers

SDS Prepared by:

ChemTel
 1305 North Florida Avenue
 Tampa, Florida USA 33602-2902

(Cont'd. on page 11)

Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: April 23, 2020

Trade name: 220 Color Seal H2O Pro

(Cont'd. of page 10)

Toll Free North America 1-888-255-3924 Intl. +01 813-248-0573
Website: www.chemtel.com