



ICT TECHNICALS

# Ure Shades

(Semi-Transparent Color Additive for Ure-Seal H2O)

Item# 155

## USE:

*Ure Shades* is a semi-transparent, concentrated, color pack additive to be used in conjunction with *Ure-Seal H2O*. Using *Ure Shades* with *Ure-Seal H2O* gives the ability to seal and recolor all in one, simple process.

## DESCRIPTION:

*Ure Shades* is a quick and easy way to restore color or recolor any properly prepared, cementitious substrates. Any surface that Ure-Seal H2O can be used is suitable for Ure Shades. Brick pavers, driveways, stamped concrete, faux rock waterfalls, interior floors, and more are perfect for Ure Shades and Ure-Seal H2O. The colors available match the existing color chart for Water Shades, semi-transparent water-based stain. Refer to [www.InnovativeConcrete.com](http://www.InnovativeConcrete.com) for color selector. Keep in mind that digital imaging will vary between devices and is meant to be used as a close representation but may not be exact.

## FEATURES & BENEFITS:

Ure Shades combined with Ure-Seal H2O will color and seal a surface with one easy process. Renovations, restorations, and new installs are quick and easy when using Ure Shades and Ure-Seal H2O semi-transparent coloring system together.

Available in 10 colors; Barnacle, Brick Red, Canyon Brown, Coral Dust, Desert Gold, Granite Gray, Red Clay, Sage Green, Slate Black, and Saddle Tan.

## INSTRUCTIONS FOR USE:

**Mixing instructions:** 1.) Add 30 oz of Ure Shades to the Part A of a 5-gallon kit of Ure-Seal H2O and mix thoroughly. 2.) Add Part B to the tinted mixture and mix thoroughly again. 3.) Dilute the mixture of Ure Shade, Part A, and Part B as necessary for specific job installation.

Installation consists of 1-2 coats of the Ure-Seal H2O and Ure Shades mixture, or until desired color is achieved. Spray application is required.

Refer to Ure-Seal H2O Technical Data Sheet for additional information on mixing instructions, surface preparation, and installation instructions.

Always apply a test area for best results.

## PRECAUTIONS:

May be harmful if swallowed

Avoid contact with eyes

Cleans up with sodium bicarbonate & water, wax floor stripper, or Total Quick Strip S/R or M/L

## **Keep Out Of Reach Of Children**

**WARNING!** This product contains chemicals known to the state of California to cause cancer and birth defects or other reproductive harm.

## ICT Corporation

2410 McJunkin Road \* Lakeland, FL 33803

(Nationwide): 888-296-5236 \* (Local): 863-665-8787 \*(Fax): 863-666-2768

(Email): [info@innovativeconcrete.com](mailto:info@innovativeconcrete.com)

[www.innovativeconcrete.com](http://www.innovativeconcrete.com)

All Innovative Concrete Technology Corp. products are manufactured with the finest raw materials. Shelf life is 2 years from the date of manufacturing when maintained in protected storage of 50°F to 90°F. It is the applicator's responsibility to determine the appropriate use of the product. All recommendations and suggestions are made without warranty, express or implied, since conditions of use are beyond ICT's control. ICT Corp. disclaims any liability incurred in connection with the use of these data or suggestions.

Rev: MAR. 2020