



ICT TECHNICALS

# Total Quick Strip ML

Item # 770-5G

**DESCRIPTION:**

*ICT Total Quick Strip ML* is an environmentally friendly, heavy duty, professional high performance paint/coatings stripper. *Total Quick Strip ML* is a non-hazardous, water based, ultra low V.O.C. stripper that can be used for interior and exterior applications. *Total Quick Strip ML* does not contain methylene, MEK, NMP, or any other harsh chemicals, therefore making it more user friendly than strippers historically used for the same purposes. *Total Quick Strip ML* will aid in removing multiple coats solvent based acrylic, water based latex, urethane, varnish, lacquer, adhesives, and other floor finish build-ups.

**FEATURES & BENEFITS:**

- Commercial strength
- Non MEK
- V.O.C. compliant in all 50 states
- No neutralizing
- Horizontal application
- Vertical application
- Non caustic
- Concrete/masonry

**APPLICABLE SURFACES:**

- Brick and Clay Pavers
- Natural Stone
- Metal
- Wood
- Plastic
- Fiberglass

**PREPARATION:**

Test an area to determine effects and dwell time before use. Always work in manageable areas at a time. Pre-clean area and allow to dry prior to application. Protect all plants and vegetation. Mask off all surfaces that you do not want to come in contact with **Total Quick Strip ML**. **DO NOT DILUTE.**

**APPLICATION:**

Shake well before use. Do not dilute. Apply *Total Quick Strip ML* liberally to a dry surface with a brush, roller or squeegee and allow to dwell a minimum of 30 minutes. Depending on the temperature, type of coating, and number of coats, dwell time will vary from 30 minutes to 12 hours (typically between 30-45 minutes). Do not allow product to dry before removing coating. Cover areas you do not want stripped cover with plastic or visqueen. Once *Total Quick Strip ML* has started to lift coating from surface, scrape off residue and dispose of according to local, state, and federal regulations. Once coating is removed be sure to clean the surface area of all remaining residues by scrubbing, rinsing, power washing, etc. Some coatings may require additional applications and dwell time. Do not allow *Total Quick Strip ML* to dry. If surface appears to be drying, roll out more *Total Quick Strip ML*. **DO NOT KEEP WET WITH WATER.** Introducing water will neutralize *Total Quick Strip ML*, negating any progress made in the stripping process.

**COVERAGE:**

Coverage will vary due to the type of coating/product being removed, temperature, and application methods, but is generally between 50-150 Sq Ft. per gallon.

**CHARACTERISTICS AND TECHNICAL DATA**

<u>Liquid Properties</u>	<u>Test Result</u>
Appearance Wet.....	Milky White
Odor.....	Mild
Weight Per Gallon.....	8.70
V.O.C.....	40 G/L
Coverage.....	50-150 sq. ft/GAL
Shelf Life.....	1 Year
Packaging....	5 gallon

(cont'd on reverse)

**ICT Corporation**  
 2410 McJunkin Road \* Lakeland, FL 33803  
 (Nationwide): 888-296-5236 \* (Local): 863-665-8787 \*(Fax): 863-666-2768  
 (Email): info@innovativeconcrete.com  
 www.innovativeconcrete.com

All Innovative Concrete Technology Corp. products are manufactured with the finest raw materials. Shelf life is 1 year from the date of manufacturing when maintained in protected storage of 50°F to 90°F. It is the applicator's responsibility to determine the appropriate use of the product. All recommendations and suggestions are made without warranty, express or implied, since conditions of use are beyond ICT's control. ICT Corp. disclaims any liability incurred in connection with the use of these data or suggestions.

REVISED 8/11/2022

ICT TECHNICALS

# Total Quick Strip ML

Item # 770- 5G

## CLEAN UP:

Clean up all equipment with warm soap and water or denatured alcohol.

## PRECAUTIONS:

DO NOT STORE OR COLLECT ANY REMOVAL OR PAINT RESIDUE IN METAL CONTAINERS. USE ONLY PLASTIC CONTAINERS. KEEP OUT OF REACH OF CHILDREN. DO NOT TAKE INTERNALLY. STORE AT ROOM TEMPERATURE. KEEP FROM FREEZING.

## FIRST AID:

**IF INGESTED:** If conscious, rinse out mouth with water and give 1 glass of water to dilute. Do not induce vomiting unless directed by medical personnel. Get immediate medical attention. **IF CONTACT WITH EYES:** Flush eyes with water for at least 20 minutes. Get immediate medical attention. **IF ON SKIN:** Wash thoroughly with soap and water. Remove contaminated clothing and wash before reuse. If skin irritation occurs seek medical attention. **IF INHALED:** Remove person to fresh air. If breathing has stopped give artificial respiration. Get immediate medical attention.

**DANGER: Eye, skin, and respiratory irritant. Always use proper personal protective equipment. Avoid breathing fumes, mist, or vapors. For professional use only. Refer to Safety data sheet for additional information.**

**CALIFORNIA PROPOSITION 65: This product contains a chemical known to the state of California to cause cancer and/or reproductive toxicity.**



ICT Corporation: 2410 McJunkin Road \* Lakeland, FL 33803  
(Nationwide): 888-296-5236 \* (Local): 863-665-8787 \*(Fax): 863-666-2768  
(Email): [info@innovativeconcrete.com](mailto:info@innovativeconcrete.com)  
[www.innovativeconcrete.com](http://www.innovativeconcrete.com)

REVISED 8/11/2022